



<p><b>Basic Series</b></p>	<p><b>OUTPUT</b></p> <p>(12) IEC 60320 C13 (10A Rated)</p> <p>(6) IEC 60320 C19 (16A Rated)</p>	<p><b>OPERATING TEMPERATURE</b></p> <p>0° to 60°C</p>
<p><b>INPUT</b></p> <p>250VAC 32A 50HZ</p> <p>IEC60309 32A Commando plug</p> <p>3M H07RN-F3G4mm² Power lead</p>	<p><b>BRANCH CIRCUITS</b></p> <p>(2) 16A Overload</p>	<p><b>MOUNTING ACCESORIES</b></p> <p>(2) IPFIX001</p> <p>(2) IPFIX002</p> <p>(2) IPFIX003</p>

<p>DRAWING TYPE</p>  <p>(NO PERMISSION, NO CHANGING)</p>		<p>ENIECO45120632AV</p>	
<p>TECHNICAL STANDARD</p> <p>1.IT11;</p> <p>2.NO RUSTNESS</p> <p>3.NO FLAW ON THE SURFACE</p>		<p><b>MATERIAL:</b></p> <p>Aluminum</p> <p>Black Powder Coat</p>	
<p><b>FILLET</b></p>	<p>R0.5</p>		
<p><b>ANGLE</b></p>	<p>±0.5°</p>		
<p><b>FIRST ANGLE</b></p> 			
<p>SCALE 1:3</p>		<p>DATE 18-01-2017</p>	