




<p><b>Basic Series</b></p>	<p><b>OUTPUT</b></p> <p>(4) C19 Socket (16A Rated)</p>	<p><b>OPERATING TEMPERATURE</b></p> <p>0° to 60°C</p>
<p><b>INPUT</b></p> <p>250VAC 32A 50HZ IEC60309 32A Plug 3M H07RN-F3G4.0mm<sup>2</sup> Power lead</p>	<p><b>BRANCH CIRCUITS</b></p> <p>(2) 16A Breaker</p>	<p><b>MOUNTING ACCESORIES</b></p> <p>(2) 46 Bracket</p>

Revisions		
Rev	Description	Date

<p>DRAWING TYPE</p>  <p>(NO PERMISSION, NO CHANGING)</p>		<p>IECCB460432AH</p>	
<p>unit=mm</p>		<p>Housing</p>	<p>Aluminium</p>
<p>TECHNICAL STANDARD 1.IT11; 2.NO RUSTNESS 3.NO FLAW ON THE SURFACE</p>			<p>Black Powder coating</p>
<p>FILLET R0.5</p>	<p>ANGLE ±0.5°</p>		
<p>FIRST ANGLE</p> 			
<p>SCALE 1:3</p>		<p>DATE 29-05-2015</p>	