




| | | |
|---|---|---|
| <p>Basic Series</p> <p>Current Meter</p> | <p>OUTPUT</p> <p>(2) C19 Locking (16A Rated)</p> | <p>OPERATING TEMPERATURE</p> <p>0° to 60°C</p> |
| <p>INPUT</p> <p>250VAC 16A 50HZ IEC60309 16A Plug 3M H05VV-F3G1.5mm² Power lead</p> | <p>BRANCH CIRCUITS</p> <p>(NONE)</p> | <p>MOUNTING ACCESORIES</p> <p>(2) 46 Bracket</p> |

| Revisions | | |
|-----------|-------------|------|
| Rev | Description | Date |
| | | |

| | | | |
|---|---------------------------|---|-----------------------------|
| <p>DRAWING TYPE</p>  <p>(NO PERMISSION, NO CHANGING)</p> | | <p>IECLKM460216AH</p> | |
| <p>unit=mm</p> | | <p>Housing</p> | <p>Aluminium</p> |
| <p>TECHNICAL STANDARD 1.IT11; 2.NO RUSTNESS 3.NO FLAW ON THE SURFACE</p> | | | <p>Black Powder coating</p> |
| <p>FILLET R0.5</p> | <p>ANGLE ±0.5°</p> |  | |
| <p>FIRST ANGLE</p>  | | | |
| <p>SCALE 1:3</p> | | <p>DATE 29-05-2015</p> | |