




| | | |
|-------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| TECHNOLOGY FUNCTIONALITY 3Phase PDU | OUTPUT (12) IEC 60320 C13 (10A Rated) | OPERATING TEMPERATURE 30° to 140°F 0° to 60°C |
| INPUT 400VAC 32A 50HZ IEC60309 32A 5pin plug 3M H07RN- F5F4mm² Power lead | BRANCH CIRCUITS (6) 1 Pole Magnetic Hydraulic CB UL489 listed | MOUNTING ACCESORIES (2) IPFIX001 (2) IPFIX002 (2) IPFIX003 |

| | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|---------------------------------------------------------------------------------------|--|
| DRAWING TYPE  <small>(NO PERMISSION, NO CHANGING)</small> | | ENCB451232A3PV | |
| TECHNICAL STANDARD 1.IT11; 2.NO RUSTNESS 3.NO FLAW ON THE SURFACE | | MATERIAL: | |
| FILLET | R0.5 |  | |
| ANGLE | ±0.5° | | |
| FIRST ANGLE  | | | |
| SCALE 1:3 | | DATE 2014-08-13 | |