




<p><b>Basic Series</b></p>	<p><b>OUTPUT</b></p> <p>(9) IEC 60320 C13 (10A Rated) (9) IEC 60320 C19 (16A Rated)</p>	<p><b>OPERATING TEMPERATURE</b></p> <p>0° to 60°C</p>
<p><b>INPUT</b></p> <p>250VAC 32A 50HZ IEC60309 32A 3Phase plug 3M H07RN-F5G6.0mm<sup>2</sup> Power lead</p>	<p><b>BRANCH CIRCUITS</b></p> <p>(6) Single Pole Magnetic Hidraulic CB</p>	<p><b>MOUNTING ACCESORIES</b></p> <p>(2) IPFIX001 (2) IPFIX002 (2) IPFIX003</p>

Revisions		
Rev	Description	Date

DRAWING TYPE		ENIECCB45090932A3PV	
 <small>(NO PERMISSION, NO CHANGING)</small>		Housing	Aluminium
<p><b>unit=mm</b></p> <p>TECHNICAL STANDARD 1.IT11; 2.NO RUSTNESS 3.NO FLAW ON THE SURFACE</p>			Black Powder coating
FILLET	R0.5		
ANGLE	±0.5°		
FIRST ANGLE			
SCALE 1:3		DATE 14-05-2015	